





GS86

- Small portable wet saw with casing.
- Cuts porcelain, single-double fired, marble, granite.
- Straight | 45° bevel cuts
- Square knockouts | round knock-outs.
- Sanding | polishing.
- Maximum cut thickness of 1" in single-pass; 2" double-pass.
- 7,000 rotation | 20mm arbor.

- Gear ratio of motor disc 1 : 2.1
- Drive belt type Z90
- Heavy duty cooling pump.
- Stainless-steel body.
- Turtle shell cover to help transport and prevent damage.
- Blade size of $4\frac{1}{2}$ " or minimum size 4".

CUTTING	MITER	CUTTING	CUTTING	DIAGONAL	DIMENSIONS	UNIT NET
THICKNESS	THICKNESS	LENGTH	WIDTH	CUT		WEIGHT
18mm 25mm up to 1"	100mm 4"	∞	∞	∞	45 x 45xh 30cm 18" x 18" xh 12"	25kg 55 lbs.





ACCESSORIES



DSRDBC

Red brick dressing stone used for all diamond blades.

45 x 230xh 25 mm 1.75" x 9" xh 1"



WSGSRSP

Replacement velcro sanding disc. 100 grit for GS86.



WSBROLL

Side roller bench. Free-standing 28" x 20" work area with five rollers. Adjustable legs.



WSSQ90

Sliding square for 90° angles.